

CUADROS DE REGULACIÓN Y DISTANCIA
CABLES

CUADRO DE REGULACION										
VOLTAJE DE SUMINISTRO:					220	voltios	TABLERO:			
No DE HILOS					4					
Fases					120	voltios				
cos					0,8					
Rho					0,020	Cobre	0,017	uminio		
ALAMBRADO		DESCRIPCION	SALIDA	CARGA (VA)			BREAKER			CTO
AWG	Ø			Seccion (mm)	Distan cia (m)	Constante	Amp	polo	REG(%)	
12	1/2"	Lampara LED 60w	11	3,3	36	0,000105219	20	1	1,39	1
12	1/2"	Lampara LED 60w	13	3,3	28	0,000105219	20	1	0,71	2
12	1/2"	Lampara LED 60w	10	3,3	16	0,000105219	20	1	0,25	3
12	1/2"	TOMAS	6	3,3	24	0,000105219	20	1	1,41	4
12	1/2"	TOMAS	7	3,3	28	0,000105219	20	1	1,89	5
12	1/2"	Luces Emergencia	5	3,3	20	0,000105219	20	1	0,38	6
6	1.5"	T-MANTENIMIENTO	1	13,29	30	7,7732E-06	50	3	1,75	7-9
6	1,5"	Polipasto 2 Tn	1	13,29	35	7,7732E-06	30	2	0,82	8-10